Minipa MT-455A

TYPE:K °C

T1 25.1

T2 24.2

Dual K/J Thermometer

T1-T2 °C/°F

MODE

HOLD BL

CE

Catalogue No. ZRQSVP600

Lot No. F4SA43377

Serial No. F4SA43377 F

FC

Direct-Q® 5 UV (1/PK)

Elec. Ratings : 100-230V
50-60Hz 100VA

Catalogue No. ZRQSVP500

Lot No. F4SA43377

Serial No. F4SA43377

Milli-Q®

SmartPak® DQ 3

REF SPR00SIA1

Installation date

19 8 21

Production date 22-DEC-2020

Code 0308

Lot number F0SB66424

Certificate of quality online
www.mymilliqconsumables.com

Recyclable components
more info:www.millipore.com/ech2o

PF13697


Espresso
Serial n°
20


Serial n° 0503
20


0628
Vent Filter MPK01
Catalogue No TANKMPK01
Valid up to 12 months
PF10446
Installation
Production
Lot number


QUÍMICO
0628
Installation date
17 04 21
Production date
23-SEP-2019
Lot number
F9MA85411
PF10446


STANDBY
24.9°C
0.05
µS/cm@25°C
MΩ.cm@25°C
UV


STANDBY
63.4
µS/cm
MΩ.cm@25°C
UV


5.0
3.0
2.0
1.5
8.2
7.8
7.6
7.4
7.2
6.8


CL
5.0
3.0
2.0
1.5
1.0
0.5
pH
8.2
7.8
7.6
7.4
7.2
6.8


25.1°C
0.05
µS/cm@25°C
MΩ.cm@25°C
UV


600
500
Direct-Q® 5 UV

CALIBRAÇÃO ABNT NBR ISO/IEC 17025 - CAL 0378

PRÓXIMA CALIBRAÇÃO

28/04/24

Preenchido pelo cliente

Nº DO CERTIFICADO

FQ-15802/23

Nº DE SÉRIE

17159

CALIBRADO EM

25/04/23

CALIBRAÇÃO ABNT NBR ISO/IEC 17025 - CAL 0378

PRÓXIMA CALIBRAÇÃO

27/04/24

Preenchido pelo cliente

Nº DO CERTIFICADO

FQ-15803/23

Nº DE SÉRIE

2459

27/

29/02/24 10:25

N

0.1058cm--

Auto

24.6°C

0.047

HS/cm

Cont

0285

@ 25°C

Cal.

F1 F2 F3 F4

Digimed


24.6°C
0.05
µS/cm@25°C
MΩ.cm@25°C
UV